



DATA SHEET FOR PRINTABLE MEDIA BOARD (MATTE VELUM)

<p><b>Product Description</b></p>	<p><b>Matte Velum</b></p> <p>SBI Matte Velum has an instant dry, ink jet receiver layer on a resin coated paper that incorporates a smooth, matte surface. The combination is fused onto an acid and lignin free quality board which, when imaged, is ready for framing or display. Available in cut down sizes as well as full sheets, the product can be used in most Epson professional printers.</p>
<p><b>Product Details</b></p> <p><b>Availability in Full Sheet Sizes</b></p> <p>40" x 60" (coming soon)</p> <p>32" x 40"</p> <p><b>Or Cut Sizes:</b></p> <p>20" x 30"</p> <p>17" x 22"</p> <p>16" x 20"</p> <p>13" x 19"</p> <p>11" x 14"</p> <p>8" x 10"</p>	<ul style="list-style-type: none"> <li>• <b>Surface:</b> Matte</li> <li>• <b>Core:</b> 100% recycled paper, acid and lignin free</li> <li>• <b>Surface Coating:</b> Matte 60 degree Gardner &lt; 10%</li> <li>• <b>Whiteness:</b> &gt; 100%</li> <li>• <b>Weight:</b> 1000 GSM +/- 5%</li> <li>• <b>Optical:</b> 100%</li> <li>• <b>Density:</b> 0.84</li> <li>• <b>Thickness:</b> 1.3mm</li> <li>• <b>Printing Compatibility:</b> Thermal / Piezo Electronic</li> <li>• <b>Ink Compatibility:</b> Aqueous pigment</li> <li>• <b>Handling Recommendations:</b> Use gloves when handling media. Before finishing, allow approximately 24 hours for drying</li> <li>• <b>Storage &amp; Use Recommendations:</b> Product should be stored under cool, dry conditions in its original packaging, at a temperature of 50-86° F; relative humidity at 20-60%</li> </ul> <p><b>Notes:</b> For best results, use Aqueous pigment inks. Use of water-based dye ink will dramatically reduce image longevity.</p>